

OFFICE OF THE FULTON COUNTY ENGINEER

9120 County Road 14
Wauseon, Ohio 43567-9669

Telephone: 419-335-3816

www.fultoncountyoh.com/engineer.htm

Fax: 419-335-1091

Frank T. Onweller, P.E., P.S.
County Engineer

Rod Creager, P.E., P.S.
Chief Deputy Engineer

March 1, 2021

ADDENDUM #2

Township Road C Drainage and Resurfacing Project

RE: Revised Supplemental Specifications, Change to Bid Opening

1. Revised Supplemental Specifications

Please attach the revised supplemental specification page 32 to the proposal.
Please note the change to ITEM 203 – ROADWAY EXCAVATION AND
EMBANKMENT to include 703.16.B.

2. Change to Bid Opening

The bid opening is changed to Wednesday, March 10, 2021 at 9:00 A.M. at the
Fulton County Engineer's Office.

End of addendum.

included for this work. Asphalt or concrete for these approaches has been included under the appropriate line item, along with an additional line item for the removal of the existing material.

ITEM 203 - ROADWAY EXCAVATION AND EMBANKMENT

This work shall consist of all excavation and embankment as directed by the **ENGINEER** or as detailed in the attached set of roadway construction plans. All material for this item shall conform to 703.16.A or 703.16.B.

The **CONTRACTOR** shall be responsible for the disposal of any and all excessive and unsuitable excavated material.

ITEM 203 – EXCAVATION FOR PAVEMENT WIDENING

Excavation for Pavement Widening shall be cut with a mill to the specified width and depth as shown. No graders, dozers, backhoes or excavators will be allowed to cut the widening unless the road is to be reclaimed. The open trench shall be adequately maintained with barricades at all times. Placement of the proposed material shall follow close behind excavation operations so that the length of open trench is kept to a minimum. Any trenching across drives shall be immediately repaired so as to permit access. The trench may be left open overnight but must be adequately maintained and protected using drums with yellow lights attached. Proper drainage of the trench is the **CONTRACTOR'S** responsibility.

ITEM 253 – PAVEMENT REPAIRS

PAVEMENT REPAIRS shall be 4' wide unless otherwise specified. The **CONTRACTOR** shall use equipment that can meet the specified width, If the **CONTRACTOR** brings in equipment that exceeds the specified width, then any extra c.y. beyond the specified width will not be paid for by the County or Township and will be at the **CONTRACTOR'S** expense.

ITEM 254 – PAVEMENT PLANING

PAVEMENT PLANING shall be performed so that the milled surface is exposed to traffic for no more than 72 hours. The Proposed asphalt shall be placed as soon as possible, at a maximum of 72 hours, after the surface has been milled. If the surface is to be milled and also have deep repairs done, all must be completed in the 72 hour window. Should the **CONTRACTOR** fail to meet this requirement, the **CONTRACTOR** shall be assessed a penalty in the amount of \$500 per noncompliance road section